



Model Name


CP6501K

Unique selling point


- * Brilliant UHD resolution image quality / Support Landscape and Portrait
- * PCAP touch technology (Direct Bonding) / Embedded camera & array Mic / LAN & USB compatible with OPS
- * Support Eye-care technology (Anti-Glare / Flicker-Free / Low Blue Light) & Germ-Resistant Screen
- * Support Collaboration+ function: Duo Users / Duo Windows / Duo Boards / Duo OS
- * Built-in annotation software EZWrite 5.0 / Security software McAfee / Video conference software Blizz
- * Hassle-Free Maintenance though DMS / OTA

Panel	Screen Diagonal	65"	
	Backlight	DLED	
	Resolution	3840 x 2160	
	Aspect Ratio	16 : 9	
	Brightness	320nits	
	Contrast Ratio	5000:1	
	Viewing Angle	178 degree (H) / 178 degree (V)	
	Color gamut (x% NTSC)	72%	
	Frame Rate	60Hz	
	Response Time	8ms	
	Panel bit	10-bit	
	Light life	30,000hrs	
	Orientation	Landscape / Portrait	
Touch solution	Touch tech.	PCAP Direct Bonding	
	Number of touches	Up to 20 Point Multi-touch	
	Touch interface	Type B USB x 2	
	Resolution	32767 x 32767	
Cover glass	Thickness	Tempered, 3 mm	
	Hardness	7H	
	AG coating	80%	
Speaker	Built-in speaker	Built-in speakers 16W x 2 & subwoofer 15W x 1 (HIFI 2.1)	
Interface	Input	Power (AC) Inlet	x 1
		Audio line-in / Mic in (3.5mm)	x 1
		D-sub	x 1
		Type A HDMI 2.0	x 3
		Type A USB (Playback)	x 6 (USB 2.0 x 3 + USB 3.0 x 3)
		Type B USB (Touch Port)	x 2
		RS232	x 1
		LAN	x 1
	Output	Type A HDMI out	x 1
		Line out (3.5mm)	x 1
		SPDIF	x 1
	Others	Camera	x 1
		Array Microphone	x 6
		NFC Reader/Writer	x 1
		Motion Sensor	x 1
		Air Quality Sensor	x 1
		Light Sensor	x 1
		IR receiver	x 1
		OPS Slot	x 1
		WiFi Module Slot (USB 2.0)	x 1
Mechanical	Dimension (WxHxD) (Without Packing / With Packing)	1502.7 x 908.2 x 85.2mm / 1697 x 1039 x 220mm	
	Net Weight/Gross Weight	45Kg / 57Kg ± 1.5Kg	
Power	Power supply	AC100 to 240V, 50 to 60 Hz	
	Power consumption	300W (Max.)	
OSD	On-Screen Display Languages	English / French / German / Dutch / Polish / Russian / Czech / Danish / Swedish / Italian / Romanian / Finnish / Norwegian / Greek / Hungarian / Spanish / Portuguese / Traditional Chinese / Simplified Chinese / Arabic / Japanese / Thai / Persian / Vietnamese / Korean / Turkish / Indonesian. (27L)	
Accessories	Standard	Remote Control	x 1 (w/ 2.4G Dongle & Battery)
		Power Cord (by region)	By Region
		Touch pen	Active Pen x 2pcs w/ Pen Holder
		Quick Start Guide	x 1
		Regulation Sheet	x 1
		Touch Cable (USB to USB)	x 1
		HDMI cable	x 1
		VGA(D-sub 15pin) Cable	x 1
		Wall mount	x 1


Input/output terminals



Wallmount



Dimension





Features

86" 4K UHD Display and one-tap video conference meeting room solution

A gorgeous Ultra HD display and smart eye-care solution with Anti-Glare screen to keep the high quality of the meeting. It also embedded a camera & array Mic to let users could initiate a video conference immediately.

Capacitive Touch Technology Direct Bonding

Fine-tuned handwriting experience is enhanced by incorporating the advanced P-cap (Projected Capacitive) touch technology. To enable accurate, precise touch responses on the screen for realistic handwriting.

Collaboration+ Unleashes Infinite Possibilities

A suite of unique features designed to maximize efficiency, productivity, and teamwork.

Duo Boards:

Connect two boards together to create one large continuous workspace, giving ample room for multiple collaborators

Duo Windows:

Partition a single board to run two applications side by side, enabling multitasking and facilitate the flow of information between different apps

Duo OS:

Simultaneously have two different operating systems (Android, iOS, macOS, and Windows) on the DuoBoard

Duo Users:

20 fingers multi-touch capability allows multiple users to collaborate on the same screen at the same time.


EZWrite 5.0 annotation tool

EZWrite 5 is an intuitive annotation solution for boosting collaboration and communication during meetings. The handwriting recognition feature allows users to instantly convert written text. With the floating tool, users can capture screenshots of anything on the screen, and take notes on top.

Hassle-Free Display Management and Security

BenQ DMS combines Device Info and Management, Apps Management and OTA (Over-the-Air) Update to provide you an ultimate device management solution for your productivity. With the build-in McAfee also ensure your data security.

Input and Output Terminals



- | | | | |
|----|--------------|----|--------------|
| 1 | USB 2.0 | 11 | HDMI OUT |
| 2 | LAN | 12 | USB 3.0 |
| 3 | AUDIO OUT | 13 | USB 3.0/1.5A |
| 4 | RS232 | 14 | USB 3.0 |
| 5 | SPDIF | 15 | TOUCH 1 |
| 6 | AUDIO IN/MIC | 16 | HDMI IN 1 |
| 7 | VGA | 17 | HDMI IN 2 |
| 8 | Power | 18 | HDMI IN 3 |
| 9 | USB 2.0 | 19 | TOUCH 2 |
| 10 | USB 2.0 | 20 | USB 2.0 |

CP860 1K

86" Interactive Flat Panel
Corporate

Specifications

Panel	Screen Size	86"
	Backlight / Lightsource	DLED
	Resolution (Pixels)	UHD 3840 x 2160 pixels
	Brightness (Typical)	350 nits
	Contrast Ratio (Typical)	1,200 : 1
	Viewing Angle (Horizontal / Vertical)	178° / 178°
	Response Time (ms)	8ms
	Color Gamut (x% NTSC)	72%
	Light Life (Typical)	30,000 hours
	Display Orientation	Landscape
Glass	Tempered Glass	3mm, Tempered Glass
	Anti-Glare & Germ-Resistant Screen	Yes
Touch	Touch Technology	PCAP Direct Bonding
	Numbers of Touch / Resolution	Up to 20 Point Multi-touch
	Touch Interface	USB B Touch Port x 2
Connectivity & Sensor	Connector	VGA x 1, HDMI 2.0 x 3, HDMI Output x 1, 3.5 mm Audio Line Input / Mic Input x 1, 3.5 mm Audio Line Output x 1, SPDIF Audio Output x 1, USB 2.0 x 3, USB 3.0 x 3, USB B Touch Port x 2, RS232 x 1, RJ45 x 1, OPS Slot x 1, WIFI Module Slot (USB 2.0) x 1
	Built-in Camera	FHD Camera x 1
	Built-in Microphone	Array Microphone x 6
	Built-in speaker	Speakers 16W x 2 & Subwoofer 15W x 1 (HIFI 2.1)
	Sensor	NFC Sensor x 1, Motion Sensor x 1, Air Quality Sensor x 1, Light Sensor x 1, IR sensor x 1
Power	Voltage	AC 100-240V~ 50 / 60Hz
	Typical (Watt)	500W (Max.)
Mechanical	Dimension (W x H x D) (mm)	1962 x 1166 x 85 mm
	Wall Mounting (VESA) (mm)	4 holes (800 x 600 mm) Screw M8 x 25 mm
	Handle	x 2
OSD	On-Screen Display Languages	English / French / German / Dutch / Polish / Russian / Czech / Danish / Swedish / Italian / Romanian / Finnish / Norwegian / Greek / Hungarian / Spanish / Portuguese / Traditional Chinese / Simplified Chinese / Arabic / Japanese / Thai / Persian / Vietnamese / Korea / Turkey / indonesia (27L)
	Remote Controller (with 2.4G dongle & Battery)	x 1
Package / Accessory	Power Cord	By Region
	Cable	VGA (5m) x 1, HDMI (1.5m) x 1, Touch (3m) x 1
	Quick Start Guide	x 1
	User's Manual Electronic File	x 1
	Touch pen	Active pen x 2 pcs with pen holder
	Wall Mount	x 1
Optional	Optional Accessory	InstaShow, WIFI Dongle, OPS, Trolley

*Specifications subject to change without notice. Please contact your local BenQ office for the full BenQ product range.

Dimensions

